



TECHNICAL DATA

PRODUCTS DATA SHEET - FLOORMAT

The information represented on this product data sheet should be used as a guideline for product selection. This data is not intended to represent, replace or be used as a proxy for a specific product sales specification. The physical properties are averages based upon limited production runs and are subject to change as additional information becomes available



ACOUSTICS PROPERTIES:

- IMPACT ISOLATION CLASS (IIC) : (72) dB, PER ASTM E-492-04
- SOUND TRANSMISSION CLASS (STC) : (67) dB, PER ASTM E-490-02



MOISTURE PROPERTIES :

- MOISTURE VAPOR TRANSMISSION RATE : (.03) lbs/1000 ft²/24 hrs, PER ASTM E-96



DURABILITY PROPERTIES:

- COMPRESSIVE STRENGTH (@ 25%) : > (11.31) /lbs./inch² PER ASTM D-3575



MISCELLANEOUS PROPERTIES:

- R-VALUE : (5) ft²-F-hr/BTU-in
- THICKNESS : (2.20) mm
- HELPS ELIMINATE MINOR SUBFLOOR IMPERFECTIONS

FloorMat™ offers consumers a professional grade product manufactured with exacting standards of performance. FloorMat™ is an effective acoustic barrier for both through the floor and footfall noise reduction and also offers moisture protection. Manufactured for ease of installation.